



HUELSTA.COM

# FONIS

### Contents

	•
Range introduction, lists of versions	2-4
Suggested combinations	5-7
Lowboards, sideboards	8-9
Highboards, cabinets	10
Wall units	11
Intermediate bookshelves, top bookshelves, wall shelves	12
Media accessories for lowboards, flat screen supports	14-15
Accessories for units, lamps	16-18
Dining, coffee tables	19
General information:	
Switch options for lamps	20-21
Special-sized products, special articles	22
Important notes: quality of walls / assembly instruction	23

Page



#### **Pieces of art**

These expressive soloists, which are both subtle and luxurious, also work perfectly in an ensemble – because they stand out without being overpowering. The cubes from the exclusive Fonis range are tapered into slim frames to create elegant fronts in smooth matt lacquer. The most eye-catching highlight, however, is the delicate frame that supports every unit.

#### Monumental light-heartedness

Above all, you will love Fonis for its uncompromising design. The elaborate architecture creates entirely new, balanced perspectives using shapes, proportions, colours and materials.

#### Individual pieces in your favourite colour

Whichever colour you prefer, we can manufacture individual units in exactly that shade. In addition to standard colours, which are actually not that standard, every imaginable colour from the Natural Colour System is also available.

#### Soloists in an ensemble

The wide choice of shapes and colours makes it easy to create a stylish interior design with these striking soloists: from a compact living room combination to an airy designer solution featuring sideboards and wall-mounted shelves.

#### And then there was light and sound

The exclusive Fonis range includes integrated solutions for lighting in open compartments and glass cabinets as well as the operation of electronics concealed within the lowboard: The remote-controlled LED lighting with colour change and the smart IR repeater set provide the finishing touch to this design concept.

### Lists of versions

Version no.	Carcase and front	Price group	Version no.	Metal substructure and frame profile	Price group
1058 1685 2208 0664 RALM	Pure white lacquer Grey lacquer Silk grey lacquer Anthracite lacquer Free colour choice according to the RAL colour system		2332 2333 0464	Quartz structured lacquer Anthracite structured lacquer High-gloss chrome	I I

#### **Changing versions**

Colour combinations within individual units are possible. In this case please state the model number clearly and separately in the order! If versions from different price groups are exchanged, the higher price group is always charged.

Free colour choice according to the RAL colour system

### The RAL colour system

Determine almost any desired colour and colour combination yourself – it's easy with the RAL colour system. RAL colours are standardised colours that are assigned a unique number and are used in a number of colour systems and colour catalogues that are used worldwide. No matter which colour you choose: every colour trend finds the ideal application in this collection from hülsta.

#### Note on "Blue Angel" (RAL-UZ 38) and Emissions label of DGM (Class A)

It is possible that the requirements of the "Blue Angel" and the DGM Emissions Label cannot be met by some of the lacquer colours in price groups III and IV, depending on the colour mix (surface ratio of these colours in the corresponding order). However, the legal requirements are definitely met in all cases!

### Important notes

Glass versions: Glass fronts, glass shelves behind fronts and glass shelves of bookshelves of clear glass.

Metal substructures, frame profiles: Metal substructures and frame profiles in quartz structured lacquer, anthracite structured lacquer or high-gloss chrome. Please state the required version clearly in the order! Metal substructures incl. plinth adjusters.

#### Standard interior fittings:

Fitted wooden shelves are fitted behind doors at 2 Raster intervals and fitted glass shelves are fitted behind glass doors.

#### Drawer frames in standard grey.

Wall units:

Wall units always incl. wall bracket

Combinations of floor and wall units:

If floor and wall units are combined within an arrangement, there must not be any skirting boards in the room near the floor units, otherwise they must be removed.

Max. load: Max. load of wooden and glass shelves (up to 70.4 cm width) as well as drawers: 25 kg Max. load of wooden and glass shelves (between 70.4 and 105.6 cm width): 15 kg; from 105.6 cm width: 10 kg

Max. load of cover shelves: 35 kg per metre length for floor units.


Please also note any existing maximum load information for individual units which may be stated later, the general load information for wall units as well as the important notes on the quality of walls at the end of this type list.

hülsta-Push-to-open: Drawers, flaps and doors with hülsta Push-to-open

#### Information on the sketches

#### Split drawer frames:

Split drawer frames are used for drawers in front widths of 140.4 cm, 175,6 cm and 210,8 cm (the partitions are shown by dotted lines in the sketches). The front widths of the drawers are illustrated at the sketches of the units so that you can order suitable accessories for the drawers.



#### Wall units

If lowboards are included as wall units, a maximum load per unit of 15 kg per metre must not be exceeded for reasons of stability! Max. load 15 kg per metre:

181.8 cm width: 25 kg 217.0 cm width: 30 kg 252.2 cm width: 30 kg 287.4 cm width: 35 kg The wall units can only be fitted on absolutely solid walls. Light masonry is not suitable for this purpose.

For each project please remember to leave a 2.0 cm gap at the top to be able to mount units.

# Labelling in type list drawings / assembly notes for wall units

Labelling in type list drawings /

assembly notes for wall units The majority of units have two wall mounting points (= number of base plates), if these are to be fitted as wall units. This is not explicitly mentioned in the type list. If a different number of wall mounting points (= base plates) is required, this is marked in the drawings in the type list with numbers in black boxes. Please be sure to note here the information and notes in the "Wall composition" chapter! Notes on delivery

Notes on delivery:

3 4

The majority of the units are delivered standard as fully connected units (glued) so that the carcase cannot be disassembled. There are however some exceptions to this rule:

Some carcases are delivered as complete units but can be <b>disassembled into</b> individual sections in the final customer's home. These types are marked with a <b>1</b> in the type list.	1
--	---

2


Some carcases are delivered **in individual sections** because of their size. These types are marked with a **2** in the type list.

The fronts with the number  ${\bf 2}$  are delivered separately and can therefore always be (dis-) assembled.


### Wall fitting

**Important notes:** Generally speaking, you as a dealer/qualified fitter are responsible for the correct wall mounting of the units. That is why wall mounting should only be carried out by properly trained and qualified fitters. hülsta supplies materials for mounting units on walls for nearly all the units and which should be used for safety and for constructional reasons. The assembly materials supplied by hülsta (plugs, screws) are only suitable for fitting components on to concrete in firmness class C12/15. For other materials (please see separate materials table in the wall composition chapter) we provide you with an assembly

For other materials (please see separate materials table in the wall composition chapter) we provide you with an assembly mortar set as an extra order. Please note that this assembly mortar set is also only suitable for the materials listed in the materials table. If walls are made up of other materials (e.g. plastered or lighter wall materials), one should use another method of mounting better suited to the load on site. Please note that if the units are not mounted properly on the wall, there is a risk of the units falling down or tipping over – especially when alternative mounting materials acquired on site have been used. For the reasons stated above it is absolutely essential to enquire about the composition of any walls before signing any contracts.



### **Suggested combinations**



E 7.2023

FONIS


### Suggested combinations

6

As an alternative to planning an individual unit from the complete range there is the possibility of choosing from specially suggested combinations. This eases planning. Incorporating accessories can enhance the suggested combinations. These are charged extra. 73,0 73,0 57,2 57,2 145 252,2 + 252.2 8 ម្ព Surcharge for frame profile in high-gloss chrome Surcharge for frame profile in high-gloss chrome 980014 as illustr. v. versa 980015 981014 981015 Price gr. Ī 74,8 145 145 252,2 287,4 + 45 - + 35 + Surcharge for frame profile and metal substructure in high-gloss chrome Surcharge for frame profile and metal substructure in high-gloss chrome as illustr. v. versa 980003 981003 980010 981010 Price gr. . III 37,8 + + 37,8 37,8 יית ה 37,8 🔶 + 57,2 180,2 180.2 287, + 45 + 35 + Surcharge for frame profile and metal substructure in high-gloss chrome Surcharge for frame profile and metal substructure in high-gloss chrome as illustr. v. versa 980016 980004 981016 981004 Price gr. \_ \_ 

# Suggested combinations


## FONIS




.7

### Lowboards and sideboards

8






Wohnen: FONIS

9

## Highboards

Highboards			100.0				
108.2 resp. 143.4 cm high (110.0 resp. 145.2 cm high incl. 1.8 cm high plinth adjusters),				cm high frame profile in s chrome	143.4 cm high Surcharge for frame profile in high-gloss chrome		
45.0 cm deep			-			-	
Cannot be fitted as a wall unit!							
	70,0 34,8		34,8	34,8         34,8         52,4         34,8         70,0         34,8		70,0 34,8	
			109.8 c	m wide	74.6 cm wide	92.2 cm wide	109.8 cm wide
			Left: 1 dooi sec Right:	tion	Left: 1 door with glass section Right: 1 door	Left: 1 door with glass section Right: 1 door	Left: 1 door with glass section Right: 1 door
		as illustr. v. versa	711 711		97511 97512	99211 99212	91111 91112
		Price gr. I III	-		-	-	-
Metal substructure incl. plinth adjusters; 54.6 resp. 19.4 cm high			54.6 cm high	19.4 cm high	19.4 cm high	19.4 cm high	19.4 cm high
The units can be planned optionally on a metal substructure. In this case the plinth adjusters are omitted.							
			for 109.8	cm width	for 74.6 cm width	for 92.2 cm width	for 109.8 cm width
			3111	2111	271	291	2111
		Price gr. I		-	-	-	

### **Cabinets**




Wohnen: FONIS

Wall units				Notes on delivery: Please see here the infor- mation on range introduction pages.	1     Assembly notes f       Please be sure to and notes in the "V	for wall units:       3         note here the information       4         Wall composition" chapter!       4	FONIS
Wall units				Surcharge for frame prof	file in high-gloss chrome		
37.8 cm high; 35.0 cm deep	70,0 34,8			105,	2 34,8	140	0,0 34,8
			cm wide	145.0 c		180.2 c	
			l glass door	1 drawer; 1		1 drawer; 1	
	as illustr. v. versa		)111 )112	214 214		218 218	
Max. load: 40 kg	Price gr. I III		-	-		-	
		1 flap; 1 g	glass door	1 flap; 1 g	lass door	1 flap; 1 g	ass door
		Flap hinge at top	Flap hinge at bottom	Flap hinge at top	Flap hinge at bottom	Flap hinge at top	Flap hinge at bottom
	as illustr. v. versa <b>Price gr.</b>	210191 210192	210181 210182	214191 214192	214181 214182	218191 218192	218181 218182
Wall units or wall assembly: See here the information on page 3		-	-	-	-	-	-
Wall units 73.0 cm high; 35.0 cm deep		1	I	Surcharge for frame prof	l III file in high-gloss chrome -		
					4 34,8	700	D 34,8
			cm wide	1	m wide	109.8 cm wide	
		1 door; 1	glass door	2 flaps; 1 glass door		2 flaps; 1 glass door	
	as illustr. v. versa	47181 47182		410281 410282		410181 410182	
	Price gr. I III		-		-	-	
				Surcharge for frame prof	file in high-gloss chrome -		
Max. load: 40 kg		70,0		105		I	
		145.0 (	cm wide	145.0 (	cm wide		
		2 flaps; 1	glass door	2 flaps; 1	glass door		
	as illustr. v. versa <b>Price gr.</b>		4281 4282		181 182		
Wall units or wall assembly: See here the information on page 3	1		-		-		
Wall units 73.0; 108.2 resp. 178.6 cm high; 35.0 cm deep	Wall units         73.0 cm high           73.0; 108.2 resp. 178.6 cm         73.0 cm high		cm high	108.2 (	cm high	178.6 c	m high
Max. load: 40 kg		34,8 L 37.8 cm wide		34,8 <b>L</b> 37.8 cm wide		34,8 37.8 cm wide	
		1	door	10	door	1 d	oor
			11 L 12 R		11 L 12 R	103 <sup>-</sup> 103 <sup>-</sup>	
Wall units or wall assembly: See here the information on page 3	Price gr.		-		-	-	-


-

\_

### Intermediate bookshelves



### **Top bookshelves**



### Wall shelves

Wall shelves 2.5 cm thick; 24.0 cm deep					
for fitting anywhere on walls					
		146.6 cm wide	181.8 cm wide	217.0 cm wide	252.2 cm wide
		Max. load: 10 kg	Max. load: 10 kg	Max. load: 15 kg	Max. load: 15 kg
		1424	1824	2124	2524
Priv I III	ice gr.	:		-	
ED lamps for wall shelves			LED lamps incl. footswit	ch. A remote control unit is possible for	operation (against a surcharge).
his product contains a ght source of energy fficiency class F. 12 V.			، ۱/۱ /۱/ /۱/ /۱/ /۱/ /۱/	1 /1 /1 /1 /1 /1	
		for 146.6 cm width	for 181.8 cm width	for 217.0 cm width	for 252.2 cm width
		10.1 W	13.4 W	16.8 W	20.4 W
		145	175	215	245
		-	-	-	-





E 7.2023

### **IR repeater set**

#### **IR repeater set**

Infrared signal transmission set for operating media units behind non-transparent fronts. You can operate all the units in one compartment with one set. The following applies:

- One set must be used in each compartment. 2 transmitters can also be installed in large compartments in order to increase performance. In this • case only one additional transmitter needs to be ordered. The transmitter must be placed in the direct vicinity of the receiver eye.
- •
- •
- Transmittable IR frequency band 20 60 kHzUp to 3 transmitters can be combined with one receiver. •

It is possible to use 3 transmitters via 1 receiver including Master box. This enables simultaneous operation of 3 different furniture compartments or in to operate 2 end units placed next to one another.

The IR repeater set consists of:

- 1 receiver eye (Ø 3.0 cm) incl. standing bracket ۰
- 1 electrical transmitter
- 1 plug EVG 12 V •
- Cable clips

Please note the details stated in the operating instructions!



	<b>Cable aperture K1</b> silver-coloured; Ø 8.0 cm It is possible to fit a cable aperture in the top shelf of the lowboard. The cable aperture can be made at the rear of the top shelf. The position is in the centre of the compartment, distance from centre of aperture to rear edge of unit: 10.0 cm.	K1
0	<b>Cable aperture K2</b> silver-coloured; Ø 8.0 cm It is possible to fit a cable aperture in the rear wall of the lowboard. Positioned in centre of compartment.	K2
	<b>Cable aperture K7</b> silver-coloured; 7.0 x 12.0 cm It is possible to fit a cable aperture in the top shelf of the lowboard. Positioned in centre of compartment, flush with the rear edge of the unit.	K7 -
	<b>Cable aperture K8</b> silver-coloured; 12.8 x 3.2 cm It is possible to fit a cable aperture in the top shelf of the lowboard. The cable aperture can be made at the rear rim of the top shelf. Positioned in centre of compartment.	K8 -
	<b>Cable aperture K9</b> 13.0 x 1.6 cm It is possible to fit a cable aperture in a fitted shelf. The cable aperture can be made at the rear rim of the fitted shelf. Positi- oned in centre of compartment.	K9 -
	<b>Cable aperture K20</b> silver-coloured; Ø 8.0 cm It is possible to fit a cable aperture in the partitions of the lowboard. Position: Distance from centre of aperture to rear edge of unit: 10.0 cm.	K20

IR repeater set


1 receiver eye and

1 transmitter incl. standing bracket

2001

Extra transmitter 2003

### **Flat screen supports**



### **Accessories for drawers**

			for 34.8 cm front width	for 52.4 cm front width	for 70.0 cm front width	for 105.2 cm front width	for ½ drawer, 140.4 cm wide, and 70.0 cm front width	for ½ drawer, 175.6 cm wide, and 87.6 cm front width	for ½ drawer, 210.8 cm wide	
	Tableau	for 35.0 cm depth			8627	8628	8629			
	lined with grey fabric	for 45.0 cm depth	8620	8621		8623	8624	8625	8626	
			17.6 cm wide				35.2 cm wide			
	<b>Cutlery box</b> of metal, lined with grey fabric ir incl. compartments	nside;								
			855				-			
			Set 1: for stan	idard cutlery like sp	ooons, forks, knives,	etc.	Set 2: for sauce ladle	s, cake forks, cake s	servers, etc.	
Cutlery holder lined with grey fabric, for fitting in drawers Set 1: for 60 pieces of cutlery Set 2: for 17 serving utensils		in								
				116 -				117 -		

### **Fitted shelves**

				for 34.8 cm front width	for 52.4 cm front width	for 70.0 cm front width	for 105.2 cm front width	for ½ compart- ment behind 140.4 cm wide flaps	for ½ compart- ment behind 175.6 cm wide flaps	for ½ compart- ment behind 210.8 cm wide flaps
		for 35.0 cm depth		144	152	162	1102	172		
			Price gr. I III	-	-	-	-	-		
	Fitted shelf 1.9 cm thick (2.8 cm thick for	for 45.0 cm depth		134	164	174	1103	163	183	1113
	105.2 and 210.8 cm front width)	doput	Price gr. I III			-	-	- -		-
		for wall units type 47181 and 47182		154						
Glass shelf (clear glass)		<u> </u>	for 35.0 cm depth	- 324		364				
	0.8 cm thick	ass) hick		334 -	354 -	374 -				

### Accessories for units

Lamps		LED lamps incl. footswitch. A remote control unit is possible for operation (against a surcharge).			
	<b>Integrated LED spotlamp</b> Ø 7.1 cm; for fitting in units Later fitting is not possible.		2.9 W		
	This product contains a light source of energy efficiency class F. 12 V.		7941		
	LED light panel	for 35.2 cm width	for 52.8 cm width	for 70.4 cm width	
11 11 under glass shelves	1.9 cm thick, 3.0 cm deep; for fitting under glass shelves Later fitting is not possible.	2.4 W	3.5 W	5.1 W	
	This product contains a light source of energy efficiency class F. 12 V.	325	525	825	
		for intermediate bookshelf type 2701	for intermediate bookshelf type 4701 and top bookshelf type 4711	for top bookshelf type 6711	
7	LED frame profile lamp LED lamp fitted in the frame profile of intermediate and top bookshelves	6.8 W	13.5 W	20.2 W	
7	Later fitting is not possible.				
	This product contains a light source of energy efficiency class F. 12 V.	725	745 -	765 -	

### Radio remote control with change of colour temperature

The lamps are normally operated by an external foot switch. The colour temperature of the LED lamps is cold white if a foot switch is used. A 4-channel radio remote control is also available as an alternative, which is charged extra. Several lamps can be operated with each of the 4 channels. All 4 channels can be dimmed separately at the push of a button. The colour temperature of all 4 channels can be set to any level from cold white (approx. 6500 kelvin = the basic setting of the LED lamps) to warm white (approx. 2700 kelvin). If warm white is required, a radio remote control must be ordered. It is also possible to switch all channels on and off simultaneously with the "all on" or "all off" buttons. The radio remote control consists of one transmitter and one receiver. If several receivers are required because of the arrangement of the units, these and the corresponding cables are provided ex-works (no surcharge). The foot switch is omitted when the radio remote control is used.

hülsta X

2119

### **DINING** Dining tables and chairs

### FONIS

#### DINING

hülsta offers a room concept to meet all requirements in comfort, beauty of form and attractiveness with a comprehensive collection of dining room tables and chairs.

The **dining tables** in a wide variety of sizes (with and without pullout function) in all wood surface versions and in contemporary designs, as well as the **dining chairs** that can be combined individually using different armrests, comfort features, high-grade cover fabrics (leather, textiles) and metal surfaces can all be found in the "**DINING**" type list.

### Coffee tables / ancillary table CT 250

#### Coffee tables / ancillary table CT 250


The CT 250 provides genuine designer pieces for your living room. Experience a glass coffee table that features two table tops, thus providing ample storage. Its elegant gloss chrome or powder-coated frame perfectly encases the table tops. Simply combine it with the CT 250 ancillary table, a matching, higher companion for the coffee table. Its expressive frame repeats the round design shape of the table top, perfectly underlining it.

You will find the coffee table CT 250 as well as other coffee tables in the "Coffee tables" type list.

### **Coffee tables**

#### **Coffee tables**

hülsta offers a comprehensive **collection of coffee tables**, which not only match the hülsta furniture ranges perfectly but can also be combined with other products that are available on the market. You will find these coffee tables in a number of designs, sizes and versions in the **"Coffee tables"** type list.





### Radio remote control with change of colour temperature

also available as an alternative, which button. The colour temperature of all 4 kelvin). If warm white is required, a rad The radio remote control consists of or	n external foot switch. The colour temperature of the LE is charged extra. Several lamps can be operated with e channels can be set to any level from cold white (appri lio remote control must be ordered. It is also possible to ne transmitter and one receiver. If several receivers are harge). The foot switch is omitted when the radio remote	ach of the 4 channels. All 4 channels can be dimmed ox. 6500 kelvin = the basic setting of the LED lamps o switch all channels on and off simultaneously with required because of the arrangement of the units, th	t separately at the push of a to warm white (approx. 2700 the "all on" or "all off" buttons.
<ul> <li>The total wattage power of all lamps</li> <li>4 channels = 4 light groups</li> <li>1 light group = x lights</li> <li>All lamps within a light group can be</li> </ul>	nd a rear wall or under plinth shelves (at least 20 mm s included per receiver must not exceed 30 W. dimmed to the same brightness. a takes place for all lamps in all light groups. de for equipment operating on 110 V.	space required under plinth shelves).	
	4-channel radio remote control with change of co	lor temperature	
© 1 2 2 4 0 0 D hülsta №	Light colour warmer Light colour colder Channel 1 to 4 (with dimmer function) All off All on	4-channel radio remote control with change of color temperature	2119 -

### Examples of use (schematic diagrams)

### **Example 1**

#### Lights inside a unit


Channel 1 operates (and dims) all the lights in light group 1, i.e. the LED spotlamp in the left cabinet

Channel 2 operates (and dims) all the lights in light group 2, i.e. the LED spotlamps in the open compartment

Channel 3 operates (and dims) all the lights in light group 3, i.e. the LED spotlamp in the right cabinet

#### Notes:

The total wattage power of all lamps included per receiver must not exceed 30 W. The change of the colour temperature takes place for all lamps in all light groups.



### Example 2

#### Lights in units set apart


Channel 1 operates (and dims) all the lights in light group 1, i.e. the LED spotlamp and the LED light panels in the left cabinet

Channel 2 operates (and dims) all the lights in light group 2, i.e. the LED spotlamps and the LED light panels in the centre cabinet

Channel 3 operates (and dims) all the lights in light group 3, i.e. the LED spotlamp and the LED light panels in the right cabinet

Notes:

The total wattage power of all lamps included per receiver must not exceed 30 W. The change of the colour temperature takes place for all lamps in all light groups.



### **Example 3**

#### Lights in units set apart


Channel 1 operates (and dims) all the lights in light group 1, i.e. the LED spotlamps in the left, centre and right cabinet

Channel 2 operates (and dims) all the lights in light group 2, i.e. the top LED light panels in the left, centre and right cabinet

Channel 3 operates (and dims) all the lights in light group 3, i.e. the bottom LED light panels in the left, centre and right cabinet

#### Notes:

The total wattage power of all lamps included per receiver must not exceed 30 W. The change of the colour temperature takes place for all lamps in all light groups.



### **FONIS**

Special-sized products are possible on request. Please get in touch with your customer advisor.

### **Special articles**

**Cover panels** for side and top panelling of fitted wardrobes (support construction and fitting materials must be acquired on site)

Veneel match with hous can not be guaranteeu.	Basic price per order + price per m² in price group I + price per m² in price group III Veneer match with fronts can not be guaranteed.	9901 990 990	- - -
	÷		

#### **Rim veneer**

superimposed ex works or rims lacquered for veneer and lacquer versions per m. length		
in price group I	9902	-
in price group III	9902	-

#### Individual special-sized products

If the special-sized product that you require is so unusual that it cannot be illustrated with the many special sized products that we already provide and charge for, then we will quote you the price using a 33 unit type factor. In your order please state for us the relevant enquiry number and the 33 unit type factor stated.

33

#### Special colours; Note on "Blue Angel" / Emissions label of DGM

#### Special colours

All the hülsta lacquer colours are possible for nearly all the hülsta ranges. Availability and prices on request.

#### Note on "Blue Angel" (RAL-UZ 38) and Emissions label of DGM (Class A)

It is possible that the requirements of the "Blue Angel" and the DGM Emissions Label cannot be met by some of the lacquer colours in price groups III and IV (see here the different lacquer versions in the NEO range), depending on the colour mix (surface ratio of these colours in the corresponding order). However, the legal requirements are definitely met in all cases!

### **Important notes**

### Wall composition / assembly instruction

#### Important notes:

The composition of walls must be ascertained before concluding a contract and be checked by a qualified fitter before assembly takes place.


Assembly may only be carried out by a qualified fitter under careful observation of the assembly instructions.

The plastic Rawl plugs supplied by hülsta as a standard set are only suitable for concrete  $\geq$  C12/15, if the wall composition and compression strength corresponds to the table below. Under no circumstances must a unit be assembled on light masonry.

Furthermore, we provide a mounting set with assembly mortar for the types of walls listed below (see assembly mortar set below). Again, assembly must be carried out by a qualified fitter under careful observation of the wall composition and assembly instruction. The compression strength levels stated below must be met under all circumstances.

#### **Materials table**

with a description of which sets are to be used with the following types of walls:



A different and more suitable type of mounting must be chosen by a qualified fitter in all other cases. hülsta cannot accept any responsibility for the choice of any other types of mounting! Please note that if the units are not mounted properly on the wall, there is a risk of the units falling down or tipping over – especially when alternative mounting materials acquired on site have been used. Generally speaking, you as a dealer/qualified fitter are responsible for the correct wall mounting of the units.

### **Mounting sets**

Labelling in type list drawings / assembly notes for wall units
 The majority of units have two wall mounting points (= number of support boards), if these are to be fitted as wall units. This is not explicitly mentioned in the type list. If a different number of wall mounting points (= support boards) is required, this is marked in the drawings in the type list with numbers in black boxes. Every support board requires four mounting screws.
 I = 3 support boards
 I = 4 support boards, etc.
 One assembly mortar set is sufficient for up to a maximum of 3 support boards or 4 wall side-panels.
 Important note: Depending on the composition of the wall (see wall types illustrated above), assembly must be carried out using the special assembly mortar set and a standard trade mastic tool which are the basic essentials for safe and clean workmanship.
 Standard set
 The standard set consists of 4 plastic Rawl plugs and 4 mounting screws and is sufficient for 1 support board. The standard sets are included in the packet of fittings to match the number of support boards.

### Assembly mortar set for up to a maximum of 3 support boards consisting of:

9x injection retaining sleeve

- 9x screw-in sleeve
- 1x injection cartridge
- 2x static mixer
- 1x assembly instructions

Please use the mounting screws from the standard set (supplied free of charge).

- Example of order:
- · Add up number of support boards for all existing unit types
- Divide the sum by "3"
- Round up the result to a full number
- = Number of assembly mortar sets required

M2

#### hülsta FONIS

#### Stand: E 7. 2023

Design and concept legally protected, subject to error and alterations to construction, colour and materials by way of technological progress.

hülsta-werke · Karl-Hüls-Straße 1 · D-48703 Stadtlohn Tel. +49 (0) 2563 / 86-0 · Fax +49 (0) 2563 / 86-1000 www.huelsta.com

